

#### Advance Features Include:

- ✓ Standard Display Models: CK-12, CK-30, CK-60
- ✓ Pole Display Models: CK-P12, CK-P30, CK-P60
- ✓ High Resolution: 1/6000 NTEP Approved class III
- ✓ Large LCD displays with 6 digit pricing and weight.
- ✓ AC Adapter included
- ✓ Non-Pole Models: 4 Direct PLU keys programmable with tare and unit price!
- ✓ Pole Models: 34 Direct PLU keys programmable with tare and unit price!
- ✓ Built-In rechargeable battery: Over 100 hours of continuous use!



#### CK-Series Feature Guide

- ❑ 1/6000 Resolution, Legal for Trade Approval #04-055
- ❑ Stainless Steel platter and ABS plastic sub-platter
- ❑ Ultra Quick-Response Weight display
- ❑ Portable design: easily used in any location
- ❑ Tough high quality UV-sealed keypad
- ❑ Compact medium-sized footprint design
- ❑ Capacities: 12 x 0.002 lb / 30 x 0.005 lb / 60 x 0.01 lb
- ❑ Pole display models: CK-P12, CK-P30, & CK-P60
- ❑ User-friendly PLU programming
- ❑ Quick operation keypad for high throughput
- ❑ Function keys: 4 or 34 PLUs, Save, Tare, and Zero
- ❑ External AC adapter or AC Power Cord Models



**Technical Specifications**

<b>Models:</b>	CK-12 & CK-P12	CK-30 & CK-P30	CK-60 & CK-P60
<b>Capacity and Graduation:</b>	12 x 0.002 lb	30 x 0.005 lb	60 x 0.01 lb
<b>Maximum Tare:</b>	12 lb	30 lb	60 lb
<b>NTEP Certificate Number:</b>	Approved 1/6000 resolution, Legal for Trade, CC #04-055, (#04-055A1 Pending)		
<b>Connectivity:</b>	RS-232 Port for connection to ECR, PC, or serial Printer		
<b>Direct PLU Keys:</b>	CK-12, CK-30, CK-60		CK-P12, CK-P30, CK-P60
	4 Direct PLU keys (Tare & Unit Price)		34 Direct PLU keys (Tare & Unit Price)
<b>Liquid Crystal Displays (LCD):</b>	Weight: 6 Digits,	999.999 max	
	Unit Price: 6 Digits,	9999.99 max	
	Total Price: 6 Digits,	9999.99 max	
<b>Platter Size:</b>	Width: 300 mm / 11.8"	Length: 225 mm / 8.9"	
<b>Accreditation:</b>	NTEP Class III, OIML, CE, ISO 9002, UL®		
<b>Product Dimensions:</b>	CK-12, CK-30, CK-60		CK-P12, CK-P30, CK-P60
	Height: 125 mm / 4.5"		Height: 575 mm / 22.6"
	Length: 340 mm / 13.4"		Width: 320 mm / 12.6"
<b>AC Specifications:</b>	Internal Power Supply, (AC Cord)		External Adapter
	120 Volts AC @ 60 Hz, AC Power Cord		120 Volts AC @ 60 Hz to 9VDC @ 800 mA
<b>Battery Specifications:</b>	100 hrs with Backlight Off or 48 hrs with Backlight On (Continuous use.)		
<b>Power Consumption &amp; Fuse Rating:</b>	Approximately 10 Watts / Fuse: 250 Volts, 1.5 Amp, 20 mm		

**Options**

<input type="checkbox"/> Foreign Power Cords & AC Adapters Available	<input type="checkbox"/> Fish Tray Optional Platter
<input type="checkbox"/> Cigarette Lighter Car Adapter, (For External Adapter models ONLY)	<input type="checkbox"/> Wet-Proof Protective Overlay



**ALGEN SCALE CORP.**

68 Enter Lane ~ Islandia, NY 11749  
 Tel: 1-800-836-8445 ~ Fax: 631-342-1977  
 sales@algen.com ~ www.algen.com

Distributed by:

\*NOTE: Specifications are subject to change without notice.